

MAGWEB SPECIFICATIONS

ME-MW-W / ME-MW-E

SAMPLE RATE

Fixed 30 second sample interval

2,800 measurements per day

COMMUNICATION – 802.15.4 XBEE WIRELESS

For use with our data.magnumenergy.com service

US version 2.4 GHz, 63 mW (+18 dBm) 300' indoor range, up to one mile line of sight outdoor range

International version 2.4 GHz, 10 mW (+10 dBm) 200' indoor range, up to 2,500' line of sight outdoor range; special order only

Low power version 2.4 GHz, 1 mW (+0 dBm) 100' indoor range, up to 300' line of sight outdoor range; special order only

Direct Sequence Spread Spectrum (DSSS)

RP-SMA connector and included rubber duck antenna

Requires 802.15.4 XBee to Ethernet wireless gateway

Wireless agency approvals
United States (FCC Part 15.247)
Industry Canada (IC)
Europe
Japan
Australia

POWER DRAW

MagWeb < 0.1 watts average from Magnum bus

Wireless Gateway < 4 watts average from 120 VAC

MATERIALS

MagWeb case ABS plastic, flame retardant, UL94V-0

Wireless Gateway case Anodized aluminum

All parts are RoHS compliant,
no lead used in manufacture

PHYSICAL SPECIFICATIONS

Shipping weight 3 lb (1.36 kg)

KIT INCLUDES

MagWeb 802.15.4
Manual
Communications cable (2-conductor, 10' twisted pair, telephone standard)
Mounting screws
Antenna

Wireless 802.15.4 Gateway
Antenna
Ethernet cable, 10'
AC adapter (Energy Star, North American plug)

REMOTE REQUIREMENTS

ME-RC or ME-ARC required when monitoring device(s) other than inverter



OFFICES

2211 West Casino Road
Everett, Washington 98204 USA
425-353-8833

4467 White Bear Pkwy
St. Paul, MN 55110 USA
800-553-6418